



ALPINE SOFT WPS

Fatliquoring Agent providing Waterproof, Touch and Fullness

Appearance	: White viscous liquid
Characteristics	: Mixture of hydrocarbons, silicones and emulsifiers
Concentration (%)	: 40,0 ± 1,0
pH Value (10 % in water)	: 6,0 - 7,0

PROPERTIES AND APPLICATION:

- Alpine SOFT WPS provides excellent homogeneous waterproofing. When used for the shoe upper leather gives fillness and tight skin.
- Alpine SOFT WPS can be used with thin light weight leather (suede, double-face, lamb, sheep).
- It can be added to retanning bath directly. It may be added to main fatliquoring dissolving 1:3 ratio in 60 °C water before fixation. It can be used in various ratios according to gain to desired effect on the skin.
- It is used for shoe upper leather desired completely waterproof with the rate of 7,0 to 8,5% over chromed weight. In order to obtain effective results neutralization pH should not exceed 5,0 and the section of the pH must be homogeneous.
- When used in fur-suede leathers provide good feather shine effect. When added after fur-suede dyeing in new bath at 45 °C and 1,0-3,0 g/L, allows formation of good touch and writing effects on suede. Fixation should be done with chromium and aluminium salts for waterproof leather.

STORAGE :

In a cool and dry place in original packaging, can be stored for a period of one year. Product must be protected from excessive heat and cold.

PACKAGING :

120 kg drums.

Technical information and recommendations contained herein, is reliable, but conditions and methods of use of our products are beyond our control not imply any warranty. We recommend to use to our customer after identified our products and the suitability of proposals of use. Tips on the use of our products be interpreted in terms of encouraging infringement of patent rights of others.

FARBEN DERİ TEKSTİL KONFEKSİYON ve KİMYEVİ MAD. TİC. Ve SAN. A.Ş.

Organize Deri Sanayi Bölgesi 19. Yol 12/6 Parsel Aydınlı Köyü – Tuzla – İSTANBUL / TURKEY

Tel: +90 216 394 11 25 Fax: +90 216 394 11 24

E-mail: info@farben.com.tr, info@herkingroup.com