



FARBEN

THE CHEMICAL PRODUCER

FARBEN FARSOFT PWP

Special Waterproof Fatliquoring Agent

Chemical Structure	: Mixture complex active emulsifier and synthetic oil
Apperance	: White fluid liquid
Concentration	: % 40,0 ± 1,0
pH Value (10 % in water)	: 6,0 - 7,0

Properties And Application :

- FARBEN FARSOFT PWP gives excellent results especially leathers desired waterproofing. Apart from it can be used at all in chromed leather that desired softness easily.
- It may be used alone or combination with anionic and neutral oil
- Even when used at low rates provides softness to skin and surface fatliquoring.
- Fixation should be done with chromium and aluminium salts for waterproof leather.

Recomended usage rates:

On shaved weight;

Furnitureleather	10,0 – 15,0 %
Waterproof shoe upper leather	8,0 – 10,0 %
Sheepgarmentleather	6,0 – 12,0 %

Storage :

In a cool and dry place in original packaging, can be stored for a period of one year. Product must be protected from excessive heat and cold.

Packaging:

120 kg drums.

Technical information and recommendations contained herein, is reliable, but conditions and methods of use of our products are beyond our control not imply any warranty. We recommend to use to our customer after identified our products and the suitability of proposals of use. Tips on the use of our products be interpreted in terms of encouraging infringement of patent rights of others.